

"TEXTURES" - HEAVY CONTRACT USE WATER-RESISTANT LVT

Product Definition		Dryback LVT		
Surface Treatment		UV, scratch-resistant coating		
Embossing		EIR (Embossed-in-Register)		
Size		Planks: 187 × 1227mm H'bone: 95 × 380mm		
Planks Per Pack		16 planks = 3.67m ²	H'bone: 24 planks = 0.8664m	
Thickness / Wear Layer		2.50mm / 0.55mm		
Micro-bevelled Edges		4 × micro-bevels per plank		
Performance Classification	EN ISO 10874	Class 33 / 42 Heavy Contract		
Residual Indentation	EN ISO 24343-1	≤0.1mm		
Reaction to Fire	EN 13501-1	Bfl-s1		
Anti-slip Classification	EN 16165:2021	SRV (dry) 65 / SRV (wet) 48		
Resistance to Staining	ISO 26987	Pass		
Reaction to Light	ISO 105 B02	≥6		
Thermal Conductivity	EN 12667	0.051 m² K/W		
Thermal Resistance	EN 12667	0.039 m² K/W		
Dimensional Stability	EN ISO 23999	≤0.15%		
Curling Resultant to Heat	EN ISO 23999	≤1.0mm		
Underfloor Heating Suitability	Yes	To maximum temperature of 27°C (80.6F)		
Castor Chair Test	EN ISO 4918	Pass		
VOC Emissions	ISO 16000	A+		
Formaldehyde HCHO Emission	EN 717-1	Class E1		
Indoor Air Comfort	Eurofins	Pass – Gold		
UKCA/CE/Floorscore		Certified		
Wear Warranty		30 year residential / 15 y	ear commercial	




Basket Weave




Diagonal Basket Weave

			_
			_
		_	
			_
_	·		

Brick



Plank / Herringbone Mix




רא צצ

(J)


PLANKS: 187 × 1227mm HERRINGBONE: 95 × 380mm

Õ-

Herringbone



Double Herringbone



Diagonal Herringbone

GEN	ER/	٩L

1111 ÉMISSIONS DANS

00000

Ĥ

Ň

 Π_{M}

ITÉRIEUR'

Cleaning, maintenance and installation	Please refer to guidance at www.textureslvt.co.uk
Laying instructions	We strongly recommend fitting is carried out by flooring professionals only and that advice is sought regarding the surface on which the LVT is to be laid and the correct adhesives to be used.
Please note	The Textures Collection has variations of colour between the planks to accentuate and enhance the unique character of real wood flooring, developed to replicate the natural beauty of the wood designs.
Warranty	Textures Embossed-in-Register LVT is backed by our 30 year Residential and 15 Year Commercial Warranty, subject to T&Cs (available on request) and are downloadable at www.texturesIvt.co.uk

floor

· · · · · ·

OSCScertified