


TEXTURES BASKET WEAVE™ — HEAVY CONTRACT USE WATER-RESISTANT LVT

Product Definition	Dryback LVT — consists of Box A (Frame) + Box B (Inserts)	
Embossing Definition	EIR (Embossed-in-Register)	
Surface Treatment	UV, matt finish	
Scratch Resistance	ISO 1518-1	Value on application. Scratch-resistant aluminium oxide.
Water Resistance	Highly water-resistant (unsuitable for wetrooms)	
Dimensions	Box A: (Frame): 95 × 380mm	Box B (Inserts): 142.5 × 142.5mm
Pieces per Pack	Box A: (Frame): 72 pcs = 2.599m ²	Box B (Inserts): 62 pcs = 1.259m ²
Pack Weight	Box A: (Frame): 11.70kg	Box B (Inserts): 5.67kg
Total Coverage	3.858m ² (Frame + Inserts)	
Thickness/Wear Layer	2.50mm / 0.55mm	
Micro-bevelled Edges		4 × micro-bevels per plank
Performance Classification	EN ISO 10874	Class 33 / 42 Heavy Contract
Anti-slip Classification	EN 16165:2021	36+ (denotes product as low risk)
Castor Chair Test	EN ISO 4918	Pass
Residual Indentation	EN ISO 24343-1	≤0.1mm
Resistance to Staining	ISO 26987	Pass
Reaction to Fire	EN 13501-1	Bfl-s1
Reaction to Light	ISO 105 B02	≥6
Thermal Conductivity	EN 12667	0.051 m2 K/W
Thermal Resistance	EN 12667	0.039 m2 K/W
Dimensional Stability	EN ISO 23999	≤0.15%
Curling Resultant to Heat	EN ISO 23999	≤1.0mm
Underfloor Heating Suitability	Yes	Water-based UFH system only to max. temp 27°C (80.6F)
VOC Emissions	ISO 16000	A+
Formaldehyde HCHO Emission	EN 717-1	Class E1
Indoor Air Comfort	Eurofins	Pass — Gold
UKCA/CE/Floorscore	Certified	
Wear Warranty	30 year residential / 15 year commercial	



















FRAME: 95 × 380mm
INSERTS: 142.5 × 142.5mm



GENERAL

Cleaning, Maintenance and Installation	Please refer to guidance at textureslvt.co.uk
Laying Instructions	We strongly recommend fitting is carried out by flooring professionals only and that advice is sought regarding the surface on which the LVT is to be laid and the correct adhesives to be used.
PLEASE NOTE	The Textures™ Basket Weave Combinations Collection has colour variations between individual pieces to accentuate and enhance the unique character of real wood flooring, specially developed to replicate the natural beauty of wood.
Warranty	Textures™ Embossed-in-Register LVT is backed by our 30-year Residential and 15-year Commercial Warranty, subject to T&Cs (available on request) and are downloadable at textureslvt.co.uk