TEXTURES STONE™ — HEAVY CONTRACT USE WATER-RESISTANT LVT

Embossing Definition Realistic Surface Treatment UV, matt finish Scratch Resistance ISO 1518-1 Value on application. Scratch-resistant aluminium Water Resistance Highly water-resistant (unsuitable for wetrooms) Dimensions 304.8 × 609.6mm (12 × 24") Tiles per Pack 16 tiles = 2.97m²	n oxide.
Scratch ResistanceISO 1518-1Value on application. Scratch-resistant aluminiumWater ResistanceHighly water-resistant (unsuitable for wetrooms)Dimensions304.8 × 609.6mm (12 × 24")	n oxide.
Water ResistanceHighly water-resistant (unsuitable for wetrooms)Dimensions304.8 × 609.6mm (12 × 24")	n oxide.
Dimensions 304.8 × 609.6mm (12 × 24")	
· · · · · · · · · · · · · · · · · · ·	
Tiles per Pack 16 tiles = 2.97m ²	
Pack Weight 13.6kg	
Thickness/Wear Layer 2.50mm/0.55mm	
Micro-bevelled Edges 4 × micro-bevels per plank	
Performance Classification EN ISO 10874 Class 33/42 Heavy Contract	
Anti-slip Classification EN 16165:2021 +36 (denotes product as low risk)	
Castor Chair Test EN ISO 4918 Pass	
Residual Indentation EN ISO 24343-1 ≤0.1mm	
Resistance to Staining ISO 26987 Pass	
Reaction to Fire EN 13501-1 Bfl-s1	
Reaction to Light ISO 105 B02 ≥6	
Thermal Conductivity EN 12667 0.051 m ² K/W	
Thermal Resistance EN 12667 0.039 m² K/W	
Dimensional Stability EN ISO 23999 ≤0.15%	
Curling Resultant to Heat EN ISO 23999 ≤1.0mm	
Underfloor Heating Suitability Yes Water-based UFH system only (max. temp 27°C/s	30.6F)
VOC Emissions ISO 16000 A+	
Formaldehyde HCHO Emission EN 717-1 Class E1	
Indoor Air Comfort Eurofins Pass — Gold	
UKCA/CE/Floorscore Certified	
Wear Warranty 30 year residential / 15 year commercial	
































TILES: 304.8 × 609.6mm (12 × 24")

GENERAL

Cleaning, Maintenance and Installation	Please refer to guidance at textureslvt.co.uk
Laying Instructions	We strongly recommend fitting is carried out by flooring professionals only and that advice is sought regarding the surface on which the LVT is to be laid and the correct adhesives to be used.
PLEASE NOTE	The Textures Stone™ Collection has colour variations between tiles to accentuate and enhance the unique character of real stone flooring, specially developed to replicate the natural beauty of stone and marble.
Warranty	Textures Stone™ Realistic Embossed LVT is backed by our 30-year Residential and 15-year Commercial Warranty, subject to T&Cs (available on request) and are downloadable at textureslyt.co.uk