



## TEXTURES STONE™ — HEAVY CONTRACT USE WATER-RESISTANT LVT

Product Definition		Dryback LVT Tiles
Embossing Definition		Realistic
Surface Treatment		UV, matt finish
Scratch Resistance	ISO 1518-1	Value on application. Scratch-resistant aluminium oxide.
Water Resistance		Highly water-resistant (unsuitable for wetrooms)
Dimensions		304.8 × 609.6mm (12 × 24")
Tiles per Pack		16 tiles = 2.97m <sup>2</sup>
Pack Weight		13.6kg
Thickness/Wear Layer		2.50mm/0.55mm
Micro-bevelled Edges		4 × micro-bevels per plank
Performance Classification	EN ISO 10874	Class 33/42 Heavy Contract
Anti-slip Classification	EN 16165:2021	+36 (denotes product as low risk)
Castor Chair Test	EN ISO 4918	Pass
Residual Indentation	EN ISO 24343-1	≤0.1mm
Resistance to Staining	ISO 26987	Pass
Reaction to Fire	EN 13501-1	Bfl-s1
Reaction to Light	ISO 105 B02	≥6
Thermal Conductivity	EN 12667	0.051 m <sup>2</sup> K/W
Thermal Resistance	EN 12667	0.039 m <sup>2</sup> K/W
Dimensional Stability	EN ISO 23999	≤0.15%
Curling Resultant to Heat	EN ISO 23999	≤1.0mm
Underfloor Heating Suitability	Yes	Water-based UFH system only (max. temp 27°C/80.6F)
VOC Emissions	ISO 16000	A+
Formaldehyde HCHO Emission	EN 717-1	Class E1
Indoor Air Comfort	Eurofins	Pass — Gold
UKCA/CE/Floorscore/EPD		Certified
Wear Warranty	<b>Residential:</b> 30-year <b>Commercial:</b> 15-year	



TILES: 304.8 × 609.6mm (12 × 24")

### GENERAL

<b>Cleaning, Maintenance and Installation</b>	Please refer to guidance at <a href="https://textureslvt.co.uk">textureslvt.co.uk</a>
<b>Laying Instructions</b>	We strongly recommend fitting is carried out by flooring professionals only and that advice is sought regarding the surface on which the LVT is to be laid and the correct adhesives to be used.
<b>PLEASE NOTE</b>	The Textures Stone™ Collection has colour variations between tiles to accentuate and enhance the unique character of real stone flooring, specially developed to replicate the natural beauty of stone and marble.
<b>Warranty</b>	Textures Stone™ Realistic Embossed LVT is backed by our 30-year Residential and 15-year Commercial Warranty, subject to T&Cs (available on request) and are downloadable at <a href="https://textureslvt.co.uk">textureslvt.co.uk</a>